

CLIMBS

DOUBLE WEBBING LANYARD WITH SNAPHOOK AND SCAFFOLD HOOKS

LCZ2W5E/015

A popular lanyard for workers who scale ladders to access machinery, silos, plant and roofs. At only 1.5m long, the ClimbS twin-tailed elasticated lanyard supports a continuous 3-point connection while climbing to reduce the risk of a fall and the compact elasticated legs provide unhindered movement.

The ZERO® energy absorption system rapidly reduces energy in a fall and the heavy-duty cover protects the lanyard from environmental damage.

RATING: 100kg LIFESPAN: 10 Years

CERTIFICATION:

EN 355:2002, AS/NZS 1891.1:2007

 $\ensuremath{\mathsf{EN}}\xspace\,355:2002$ Personal protective equipment against falls from a height. Energy absorbers

AS/NZS 1891.1:2007 Harnesses and ancillary equipment









MODEL	LENGTH	WEIGHT (G)	DIMENSIONS	MATERIAL	RATING (KG)
LCZ2W5E/015	1.5m	1.5kg	1.5m	Polyester 100%	100kg

PRODUCT FEATURES

- ZERO® Polyester energy absorption system.
- Twin rope tails.
- 12mm kernmantle static rope.
- 2x double action scaffold hooks (rated to 20kN).
- 1x snaphook connector (rated to 20kN).
- Protective energy absorber cover.
- Permitted to work in potentially explosive areas.