

SPARKPRO

DOUBLE ROPE LANYARD WITH SNAPHOOK & SCAFFOLD HOOKS FOR HOT WORKS

LSZ2RFX5

Resistant to sparks, flame and metal splash, the SparkPro is a twin-tailed lanyard made from 11.4mm aramid rope for hot works like grinding and metal cutting. Designed for continuous 3-point connection to reduce the risk of a fall, the twin-tails can be easily be adjusted to 1.2m to protect the user from a fall.

The ZERO® energy absorption system rapidly reduces energy in a fall and includes a heat-shield cover to protect from heat and sparks.

RATING: 100kg LIFESPAN: 10 Years

CERTIFICATION:

EN 354:2010, EN 355:2002, AS 4142.3-1993, AS/ NZS 1891.1:2007

EN 354:2010 Personal fall protection equipment. Lanyards EN 355:2002 Personal protective equipment against falls from a height. Energy absorbers

AS 4142.3-1993 Fibre ropes Man-made fibre rope for static life rescue lines $% \left(1\right) =\left(1\right) \left(1\right) +\left(1\right) \left(1\right) \left(1\right) +\left(1\right) \left(1\right) \left(1\right) \left(1\right) +\left(1\right) \left(1\right) \left(1\right) \left(1\right) \left(1\right) +\left(1\right) \left(1\right) \left$

AS/NZS 1891.1:2007 Harnesses and ancillary equipment











MODEL	LENGTH	WEIGHT (G)	DIMENSIONS	MATERIAL	RATING (KG)
LSZ2RFX5	1.2 - 2m	1.77kg	1.2 - 2m	Aramid rope with polyamide core	100kg

PRODUCT FEATURES

- ZERO® polyamide energy asorbtion system.
- Twin 11.4mm aramid rope tails with polyamide core.
- 2x double action scaffold hooks (rated to 20kN).
- 1x snaphook connector (rated to 20kN).
- Protective heat-shield cover.
- Resistance to flame in accordance to EN 358 P.4.1.5 Standard.

